KEL-BES brush plate

for cable pass-through



Brush plates KEL-BES for routing cables into server racks, control panels and electrical enclosures. KEL-BES is also an ideal solution for entry and exit of cables that are routed inside raised floors, e.g. in computer centres.

The brush plates can either be mounted via screws or viaexpanding rivets.

Advantages & benefits

The KEL-BES plates match exactly the cut-out dimensions 10-, 16- and 24-pin standard industrial connectors.

Specifications

| Material | Polyamide Brushes: Polyamide | Fast and easy assembly Versatile utilisation Allows reduced airflow while filtering out dust, hair and larger particulate matter |
|-----------------------|---------------------------------|--|
| Flame class | UL94-V0, self-extinguishing | Visual screening |
| Operating temperature | -20 C° to 90 C° | Protects cables against wear due to sharp edges of the cut-out |
| Properties | silicone free, halogen free | |
| Mounting options | Screw type mounting, Riveting | |

Product types & sizes

| KEL-BES 24 | Part No. EAN PU Length Width Height Mounting height | 51515 4251269315442 10 147 mm 58 mm 10 mm 10 mm | Cut-out size No. of screw holes Diam. of screw holes | 112 × 36 mm 4 5.8 mm |
|------------|---|---|--|----------------------------|
| KEL-BES 16 | Part No. | 51510 | Cut-out size | 86 × 36 mm |
| | EAN PU | 4251269315435 10 | No. of screw holes Diam. of screw holes | 4 5.8 mm |
| 1 | Length | 120 mm | | |
| | Width | 58 mm | | |
| | | 10 | | |
| | Height | 10 mm | | |

KEL-BES 10



Part No. EAN PU Length Width Height Mounting height

Cut-out size No. of screw holes Diam. of screw holes 65 × 36 mm 4 5.8 mm